



SAMURAI RANGE

SAMURAI 12V/24V ELECTRIC WINCHES



Superb high specification winch. Ideal for recovery and 4x4 applications. Outstanding features include high quality series wound double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, efficient full steel planetary gearing. Comes with stainless steel roller fairlead and fittings as standard. Complete with Heavy Duty integrated wireless remote.

FULLY SEALED 600 AMP CONTACTORS



WIRELESS CONTROL

LASER ETCHED EXTRUDED ALUMINIUM TIE BARS REINFORCED WITH STEEL BODY

FULLY SEALED TO IP 68 STANDARD



NEW HEAVY DUTY GLOSS CHIP RESISTANT FINISH

STANDARD ACCESSORIES

- Galvanised steel cable
- 3m Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook

OUTSTANDING FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover for Added Protection
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- Integrated Wireless Remote

12000 \$

RATED LINE PULL: 12 000lbs (5400kg)
MOTOR: 12v : 6.5hp / 4.6kw
GEARING: 230:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 63 x 223mm
CABLE Dia x L: 10.2mm x 26m
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 580 x 160 x 219mm

9500 \$

RATED LINE PULL: 9500lbs (4500kg)
MOTOR: 12v : 4.6hp / 3.2kw
GEARING: 230:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 63 x 223mm
CABLE Dia x L: 9.2mm x 26m
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 540 x 160 x 219mm

8000 \$

RATED LINE PULL: 8000lbs (3629kg)
MOTOR: 12v : 4.6hp / 3.2kw
GEARING: 210:1
BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 63 x 223mm
CABLE Dia x L: 8.3mm x 29m
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 540 x 160 x 219mm



\$17500 SAMURAI

17500LB 12V/24V ELECTRIC WINCH



The best £ for lb winch on the market. Outstanding features Includes Huge 7.0 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing. Stainless steel roller fairlead and fittings as standard.

**LASER ETCHED EXTRUDED ALUMINIUM
TIE BARS REINFORCED WITH STEEL BODY**



**FULLY SEALED 600
AMP CONTACTORS**



**FULLY SEALED TO
IP 68 STANDARD**

**NEW HEAVY DUTY GLOSS
CHIP RESISTANT FINISH**



STANDARD ACCESSORIES

- 3m Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware

OUTSTANDING FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Reinforced Plastic Contactor Cover for Added Protection
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads

SPECIFICATION

RATED LINE PULL: 17 500lbs (7938kg)
MOTOR: 12v : 7.0hp / 4.9kw
GEARING: 430:1
BRAKING ACTION: Automatic in the drum
DRUM SIZE Dia x L: 89 x 219mm
CABLE Dia x L: 12mm x 26m
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 610 x 216 x 254mm

TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)	Line speed		Amp draw	
		lbs (kg)	ft/min m/min	12v	24v
1	17500 (7938)	0	22.3 6.8	100	60
2	14000 (6364)	6000 (2728)	9.84 3.0	220	130
3	12500 (5682)	10000 (4545)	9.8 2.0	320	170
4	10000 (4545)	12500 (5682)	5.8 1.7	350	220
5	6000 (2728)	17500 (7938)	5.8 1.2	450	290



C3500A

3500LB 12V/24V ELECTRIC WINCH

Ideal for large ATV's and small trailers. A huge 1.95hp motor, heavy duty clutch, heavy duty steel gearing and heavy duty waterproof contactors ensure the ultimate in performance and reliability. Complete with mount plate for flat bed mounting or alternatively can be fitted to portable tow ball attachment. ATV handle bar remote available



**Comes with contactor fitted.

STANDARD ACCESSORIES

- 5.4mm x 12.8m Steel Cable
- * 3m Remote Handset
- Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- 3 Tonne Pulley Block
- Mounting plate
- Mounting Hardware
- 1/4 hook
- *ATV remote available

OUTSTANDING FEATURES

- Power in and Power out
- Quiet Efficient 1.95 hp Motor
- New Heavy Duty Clutch
- Full Steel Planetary Gearing
- H D Waterproof Contactors
- Mount Plate as Standard
- Pulley Block as Standard
- Can fit tow ball mount

SPECIFICATION

RATED LINE PULL: 3500lbs (1588kg)
MOTOR: 12v : 1.95hp / 1.37kw
GEARING: 170:1
BRAKING ACTION: Dynamic
DRUM SIZE Dia x L: 37 x 80mm
CABLE Dia x L: 5.4mm x 12.8m
MOUNTING PATTERN: 79.5mm
DIMENSIONS: 348 x 116 x 165mm
WEIGHT: 9kg

TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)	Line pull		Line speed		Amp draw	
		lbs (kg)	ft/min	m/min	12v	24v	
1	3500 (1588)	0	10.5	3.2	45	25	
2	2789 (1265)	1000 (454)	8.9	2.7	75	40	
3	2319 (1052)	2000 (907)	7.5	2.3	130	75	
4	1984 (900)	3500 (1588)	4.6	1.4	200	120	
5	1733 (786)						



C4500 EWX

4500LB 12V/24V ELECTRIC WINCH

Latest addition to the Champion Range. High quality three stage planetary gearing ensure this is one of the quietest and smoothest winches on the market. The silky smooth performance and the full load holding brake make it the perfect solution for high spec applications.



STANDARD ACCESSORIES

- 6.4mm x 14.5m Steel Cable
- 3m Remote Handset
- Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- Mounting plate
- Mounting hardware
- 3/8 hook
- *ATV remote available

OUTSTANDING FEATURES

- Power in and Power out
- High Torque 1.95hp Motor
- H D Waterproof Contactors
- Full Steel Planetary Gearing
- Mount Plate as Standard
- Full Load Holding Break
- Can fit tow ball mount

SPECIFICATION

RATED LINE PULL: 4500lbs (2041 kg)
MOTOR: 12v : 1.95hp / 1.37kw
GEARING: 172:1
BRAKING ACTION: Automatic in the drum
DRUM SIZE Dia x L: 45 x 97mm
CABLE Dia x L: 6.4mm x 14.5m
MOUNTING PATTERN: 129 x 96mm
DIMENSIONS: 360 x 126 x 165mm
WEIGHT: 13kg

TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)	Line pull		Line speed		Amp draw	
		lbs (kg)	ft/min	m/min	12v	24v	
1	4500 (2401)	0	11.6	3.6	20	15	
2	3642 (1652)	1500 (680)	9.2	2.8	70	40	
3	3060 (1388)	2500 (1134)	7.8	2.4	100	65	
4	2638 (1196)	3500 (1587)	6.6	2.0	140	80	
		4500 (2041)	4.9	1.5	200	130	